

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/262144002>

# Potential Solution to Contribute for Sugar Cane Spatial Variability Management

Conference Paper · June 2013

CITATIONS

2

READS

270

7 authors, including:



**Paulo S. Graziano Magalhães**

University of Campinas

106 PUBLICATIONS 565 CITATIONS

[SEE PROFILE](#)



**Guilherme Sanches**

Escola Superior de Agricultura "Luiz de Queiroz"

24 PUBLICATIONS 98 CITATIONS

[SEE PROFILE](#)



**Jose Paulo Molin**

University of São Paulo

208 PUBLICATIONS 977 CITATIONS

[SEE PROFILE](#)



**Gustavo Portz**

Yara International

17 PUBLICATIONS 87 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:



Metodologia para utilização de VANT no monitoramento de cana-de-açúcar para fins de Agricultura de Precisão [View project](#)



SUCRE - Sugarcane Renewable Electricity [View project](#)

## Sustainable Agriculture through ICT innovation

**Potential Solution to Contribute for Sugar Cane Spatial Variability Management**

Paulo S. Graziano Magalhães<sup>1,2</sup>, Guilherme M. Sanches<sup>1,2</sup>, José Paulo Molin<sup>3</sup>, Gustavo Portz<sup>3</sup>, Lucas R. do Amaral<sup>3</sup>, Oriel T. Kolln<sup>2</sup>, Daniel G. Duft<sup>1,2</sup>

<sup>1</sup> School of Agriculture Engineering – University of Campinas – UNICAMP, Campinas, SP, Brazil, e-mail: [graziano@feagri.unicamp.br](mailto:graziano@feagri.unicamp.br);

<sup>2</sup> Brazilian Bioethanol Science and Technology Laboratory – CTBE/CNPEN, Campinas, SP, Brazil;

<sup>3</sup> School of Agronomy – University of São Paulo – USP, Piracicaba, SP, Brazil.

**ABSTRACT**

In Brazil, the application of site-specific management in sugar cane has been delayed for many reasons, including lack of relevant technology which could really help producers increase their competitiveness. Sugar mills usually have large cultivated areas under their control, with an average size of over 40 thousand hectares. With such huge areas, it is difficult for them to find a technology that could help in the adoption of precision agriculture (PA), which enables the producer to understand and manage more precisely the inherent spatial variability found in the field, in order to obtain higher productivity and economic returns, and reduce negative environmental impacts. Vegetation Index (VI) used as an indicator of biomass can be easily obtained either by ground sensors or by orbital and non-orbital imagery obtained using an Unmanned Aerial Vehicle (UAV). The objective of the study was to evaluate the sugar cane biomass prediction using VI data obtained by means of a field sensor and an UAV on a field scale, and correlate the results with terrain and soil data. The experiment was conducted in a 30 ha sugar cane field planted in the north part of São Paulo state, Brazil on its first ratoon. Soil attributes were measured after harvesting, and biomass data was measured 90 and 180 days after crop emergence (DACE). The results showed that VI obtained by ground and non-orbital sensors have correlation with biomass production, but not with soil chemical attributes, which means that field spatial variability is more dependent of other factors than soil chemical attributes. These results could help justify the use of crop sensors and UAV by mills which could independently obtain high resolution imagery at low cost, and evaluate field conditions at the time when intervention is still possible.

**Keywords** Precision agriculture, vegetation index, field sensor, UAV, Brazil.

---

Magalhães, P.S.G., Sanches, G.M., Molin, J.P., Portz, G., Amaral, L., Kolln, O.T., Duft, G.D. "Potential Solution to Contribute for Sugar Cane Spatial Variability Management". EFITA-WCCA-CIGR Conference "Sustainable Agriculture through ICT Innovation", Turin, Italy, 24-27 June 2013. The authors are solely responsible for the content of this technical presentation. The technical presentation does not necessarily reflect the official position of the International Commission of Agricultural and Biosystems Engineering (CIGR) and of the EFITA association, and its printing and distribution does not constitute an endorsement of views which may be expressed. Technical presentations are not subject to the formal peer review process by CIGR editorial committees; therefore, they are not to be presented as refereed publications.

## Sustainable Agriculture through ICT innovation

## 1. INTRODUCTION

Sugar cane (*Saccharum* spp.) has significant importance in the tropical and subtropical regions of the world, especially for sugar and ethanol production. Recently, the sugar cane crop has been drawing global interest as a raw material for the production of energy, since it presents highly positive energetic and greenhouse gases emission (GHG) balance (Macedo, et al. 2008; Renouf, et al. 2008; Smeets et al. 2009). Brazil is the largest sugar cane producer worldwide, and its production is increasing to meet global bioethanol and sucrose demands. Although nearly 90 Mha are available for agricultural expansion in Brazil (Cerqueira Leite *et al.*, 2009), sugar cane production is increasing not only in new sugar cane areas, but more so through yield improvements in existing fields. Increases in sugar cane production are obviously related to increases in sugar cane biomass and ethanol production per unit of area. Sugar cane production is estimated to have a potential of doubling its yield per unit of area (Waclawovsky *et al.*, 2010). Adoption of precision agriculture (PA) to manage soil according to its spatial needs is a likely prerequisite to higher yields (Bramley, 2009). By combining a yield map, topographic information, maps of physical and chemical soil attributes, and imagery, it is possible to define management strategies to improve the performance of the crop, and to reduce negative environmental impacts of sugar cane production.

Data collection and evaluation methods in PA, have high operation and analysis costs, preventing its practice in certain situations, from the logistic and economical point of view. To overcome this barrier, many studies have been engaged in the development of sensors on-the-go, which may present different principles of operation, but with responses that can be indirectly related to soil mechanical, physical and chemical characteristics and plant behavior. Thus, the data acquisition can be faster, with large numbers of data at a lower cost (Peets et al. 2012).

Vegetation Indices (VI) have been developed to track the vigor of plants and can be easily obtained either by ground sensors or by orbital (satellite) and non-orbital imagery, obtained using an Unmanned Aerial Vehicle (UAV). VI has been used with success in predicting in-season N requirements for crops, using aerial color infrared photography (Sripada et al. 2006), which were taken by means of a sophisticated methodology. UAV can be an inexpensive and practical tool to obtain high resolution remotely sensed data. Although there have not been many case studies of UAV in PA, examples of its applications in environmental studies are becoming increasingly more apparent in the literature. On the same way, studies with ground sensor have demonstrated its suitability to identify sugar cane variability (Portz, et al. 2012; Molin et al. 2010). Such studies may provide insight as to how applicable these instruments may be for various PA endeavors (Zhang and Kovacs 2012).

---

**C0199**

Magalhães, P.S.G., Sanches, G.M., Molin, J.P., Portz, G., Amaral, L., Kolln, O.T., Duft, G.D. "Potential Solution to Contribute for Sugar Cane Spatial Variability Management". EFITA-WCCA-CIGR Conference "Sustainable Agriculture through ICT Innovation", Turin, Italy, 24-27 June 2013.

## Sustainable Agriculture through ICT innovation

The objective of the study was to evaluate the sugar cane biomass prediction using VI data obtained using a field sensor and low cost UAV on a field scale, and correlate the results with terrain and soil data.

## 2. STUDY AREA AND METHODS

Experiments were conducted on 30-hectare fields in Serra Azul – SP, Brazil (21.2731 S e 47.5397 W) during the first ratoon season of a sugar cane crop (CTC09). Soils on the study sites are generally uniform, Typic Quartzipsamment, by Embrapa (1999) and US Soil Taxonomy (USA, 1975). The total precipitation after harvesting, from September 2012 to May 2013, was 725 mm, and average temperatures of 25 °C.

To obtain the vegetation indices data (VI), the area was scanned in December 2012, when the cane presented three months of development and average height of 0.6 m, using as an Crop Circle active canopy reflectance sensor (ACS-210, Holland Scientific Inc. Lincoln, NE, USA) mounted on a high clearance vehicle, with a sensor measurement being taken at each 3 rows. This sensor recorded canopy reflectance in the red-edge (730 nm) and near infrared (NIR, 780 nm) wavebands at 1 Hz, connected with a GPS at the same rate. Aerial imagery was obtained by means of a UAV (swinglet CAM, SenseFly, Ecublens) using a 16MP camera (ELPH 300 NDVI, Canon, USA) with 0,012 m resolution, and interference filters with blue and green channel, and provide image in the red and NIR region of the spectrum (670 and 770 nm) obtained in 9 of May 2013.

The data generated by Crop Circle and SenseFly are in different wavelength and therefore produced different VI. For Crop Circle, the red-edge normalized differential Vegetation Index (NDRE) was calculated, and for SenseFly, green normalized differential Vegetation Index and Green Soil Adjust Vegetation Index (GNDVI and GSAVI) were calculated. Those VI cannot be directly compared, but they provide similar information about the biomass production, which can be used to evaluate field status. GNDVI is calculated using reflectance ratios in the NIR and green portion of the spectrum (Mulla 2012), the green NDVI is more sensitive to changes in chlorophyll concentration and potential crop yield than the traditional NDVI using the red waveband (Gitelson, et al. 1994). GSAVI is a transformation technique to minimize soil brightness influences from spectral vegetation indices (Huete 1988; Sripada et al. 2006).

$$\text{NDRE} = (\text{NIR}-\text{RE})/(\text{NIR}+\text{RE}) \quad (1)$$

$$\text{GNDVI} = (\text{NIR}-\text{G})/(\text{NIR}+\text{G}) \quad (2)$$

$$\text{GSAVI} = 1.5*(\text{NIR}-\text{G})/(\text{NIR}+\text{G}+0.5) \quad (3)$$

Based on the yield map obtained from the previous year, 22 points in the area were selected for biometric analysis. On each point, ten cane stalks were removed for characterization, determining the mean diameter of stalks, height, and weight of stalk, trash and tops. The data for biometric analysis was done just few days before VI data

### C0199

Magalhães, P.S.G., Sanches, G.M., Molin, J.P., Portz, G., Amaral, L., Kolln, O.T., Duft, G.D. “Potential Solution to Contribute for Sugar Cane Spatial Variability Management”. EFITA-WCCA-CIGR Conference “Sustainable Agriculture through ICT Innovation”, Turin, Italy, 24-27 June 2013.

## Sustainable Agriculture through ICT innovation

collecting (December 2012 and May 2013). The results were then compared with crop reflectance. To establish a correlation between VI and crop biometrics information, a buffer area with 3 m radius around the sampling point was created. In this buffer area, the imagery maximum value of reflectance for each band was selected to calculate the VI, and a linear correlation between this VI and crop results was evaluated.

In order to have non-yield-limiting amount of nutrients in the area, a soil survey was conducted just after harvesting in September 2012, in a 50x50 m grid (164 points). Based on the results of macronutrients, a fertilizer recommendation was done phosphorus (P) and potassium (K), for nitrogen (N) the recommendation was based on yield expectation taking into account previous year yield map. All fertilizers were applied using variable rate technology (VRT) (Uniport, Jacto, Pompéia) according to usual recommendations for sugar cane crop planting (Raij et al. 1997) 60 days after harvesting (DAH).

The geostatistic analysis were performed for all data in the study, interpolating a grid pattern of 3 m by means of Kriging site for neighboring blocks, using ArcGIS software (Environmental Systems Research Institute, Redlands, CA). Since ground collected data was less dense than UAV data, a grid based on existing point data of NDRE was used to extract data from UAV imagery to calculate GNDVI and GSAVI.

### 3. RESULTS AND DISCUSSION

Initial maps of soil chemical attributes, elevation, apparent electrical conductivity (ECa) and previous year yield provided a visual representation of the variability across the field, Figure 1. Maps were also produced from ground sensor (NDRE), and aerial sensor (GNDVI and GSAVI), Figure 2.

At the early stage of the crop development (60 DAH), the results of canopy reflectance obtained with crop circle are highly influenced by soil brightness reflectance, since the crop height was low and there are many open spaces. Nevertheless, it was possible to observe that at certain parts of the field, the biomass was more developed than others, as it can be confirmed by biometric data obtained at this stage, Table 1. GNDVI measured 180 DAH, represents better canopy reflectance since the crop was closer. At this stage there is very low soil influence, as it is seen when the data is compared with GSAVI, and very low difference is detected between these two sets of imagery. The differences among of the NDRE and GNDVIVI maps can be attributed to the different amounts of biomass at the sensing time (60 versus 180 DAH). The imagery shows that in the southern part of the field the biomass reflectance is higher, which could be an indicative that yield will also be higher in that area. It is also possible to see that in the north part of the field there are some spots with lower GNDVI, which represent lower biomass, those differences are reflected at biometric evaluation which presents a high coefficient of variation, .

---

#### C0199

Magalhães, P.S.G., Sanches, G.M., Molin, J.P., Portz, G., Amaral, L., Kolln, O.T., Duft, G.D. "Potential Solution to Contribute for Sugar Cane Spatial Variability Management". EFITA-WCCA-CIGR Conference "Sustainable Agriculture through ICT Innovation", Turin, Italy, 24-27 June 2013.






Figure 1 – Maps of some soil attributes, apparent electrical conductivity at 0.9 m, elevation and previous year crop yield.

Linear correlation between GNDVI and crop performance at this stage, measured through the biometric parameters, was established (Table 2). The best GNDVI correlation obtained was with the tops reflectance ( $r = 0.3$ ), which has a strong correlation to yield ( $r = 0.81$ ).

#### C0199

Magalhães, P.S.G., Sanches, G.M., Molin, J.P., Portz, G., Amaral, L., Kolln, O.T., Duft, G.D. “Potential Solution to Contribute for Sugar Cane Spatial Variability Management”. EFITA-WCCA-CIGR Conference “Sustainable Agriculture through ICT Innovation”, Turin, Italy, 24-27 June 2013.

## Sustainable Agriculture through ICT innovation




Figure 3 – Vegetation indices from ground and aerial sensor.

Table 1 – Results Biometric evaluation in December 2012 and May 2013

	December 2012			May 2013		
	Tillers/m	Population/ha	Mg/ha	Tillers/m	Population/ha	Mg/ha
Mean	29.6	197600	2.5	13.0	16721	16.7
Standard deviation	3.9	26439.0	0.9	2.2	6010.2	6.0
Coef. of variation	13.4	13.4	35.9	16.9	35.9	35.9

Table 2 – Linear correlation between sugar cane biometric parameters and GNDVI.

	GNDVI	Stalk				
		N° tillers/m	Tops (Mg/ha)	weight/tiller (kg)	Stalk (Mg/ha)	Total Biomass (Mg/ha)
GNDVI	1.00					
N° Tillers/m	-0.13	1.00				
Tops (Mg/ha)	0.30	0.30	1.00			
Stalk weight/tiller (kg)	0.28	-0.53	0.46	1.00		
Stalk (Mg/ha)	0.25	0.09	0.76	0.77	1.00	
Total Biomass (Mg/ha)	0.21	0.12	0.81	0.74	0.96	1.00

Although ground and aerial data were collected at different stages of the crop development, it is possible to observe that the VI has no correlation with soil attributes or field elevation.

### C0199

Magalhães, P.S.G., Sanches, G.M., Molin, J.P., Portz, G., Amaral, L., Kolln, O.T., Duft, G.D. “Potential Solution to Contribute for Sugar Cane Spatial Variability Management”. EFITA-WCCA-CIGR Conference “Sustainable Agriculture through ICT Innovation”, Turin, Italy, 24-27 June 2013.

## Sustainable Agriculture through ICT innovation

#### 4. CONCLUSIONS

Low cost UAV could be convenient to collect field data for VI determination. Although VI has only a moderate correlation with biomass production, and no correlation with soil attributes, it may be a useful tool to detect some yield tendencies in the area and places for deeper investigation of crop spatial variance causes.

#### 5. ACKNOWLEDGMENTS

The authors are very grateful to the workers of the Pedra Mill, and GeoAgri. This project was funded by FAPESP (State of São Paulo Research Foundation), FINEP (Brazilian Agency of Innovation) and CNPq (National Research Council).

#### 6. REFERENCES

- Bramley, R. G. V. 2009. "Lessons from Nearly 20 Years of Precision Agriculture Research, Development, and Adoption as a Guide to Its Appropriate Application." *Crop and Pasture Science* 60(3): 197–217.
- Cerqueira Leite, Rogério Cezar de, Manoel Regis Lima Verde Leal, Luís Augusto Barbosa Cortez, W. Michael Griffin, and Mirna Ivonne Gaya Scandiffio. 2009. "Can Brazil Replace 5% of the 2025 Gasoline World Demand with Ethanol?" *Energy* 34 (5): 655–661.
- Gitelson, Anatoly A, Yoram J Kaufman, and Mark N Merzlyak. 1996. "Use of a Green Channel in Remote Sensing of Global Vegetation from EOS-MODIS" *Remote Sensing of Environmental*, 58 (96) 289-298.
- Huete, A.R. 1988. "A Soil-Adjusted Vegetation Index ( SAVI )." *Remote Sensing of Environment* 25 (3): 295–309.
- Macedo, Isaías C., J. E.A. Seabra, and J.E.A.R. Silva. 2008. "Green House Gases Emissions in the Production and Use of Ethanol from Sugar cane in Brazil: The 2005/2006 Averages and a Prediction for 2020." *Biomass and Bioenergy* 32(7): 582–595.
- Molin, José Paulo, Flávia R Frasson, Lucas R Amaral, Fabrício P Povh, and José V Salvi. 2010. "Capacidade De Um Sensor Ótico Em Quantificar a Resposta da Cana-de-açúcar a Doses de Nitrogênio Capability of an Optical Sensor in Verifying the Sugar cane Response to Nitrogen Rates." *Revista Brasileira de Engenharia Agrícola e Ambiental* 14 (12): 1345–1349. (In Portuguese).

---

#### C0199

Magalhães, P.S.G., Sanches, G.M., Molin, J.P., Portz, G., Amaral, L., Kolln, O.T., Duft, G.D. "Potential Solution to Contribute for Sugar Cane Spatial Variability Management". EFITA-WCCA-CIGR Conference "Sustainable Agriculture through ICT Innovation", Turin, Italy, 24-27 June 2013.



## Sustainable Agriculture through ICT innovation

Mulla, David J. 2013. "Twenty Five Years of Remote Sensing in Precision Agriculture: Key Advances and Remaining Knowledge Gaps." *Biosystems Engineering*: 114: 1–14.

Peets, Sven, Abdul Mounem Mouazen, Kim Blackburn, Boyan Kuang, and Jens Wiebenson. 2012. "Methods and Procedures for Automatic Collection and Management of Data Acquired from On-the-go Sensors with Application to On-the-go Soil Sensors." *Computers and Electronics in Agriculture* 81: 104–112.

Portz, G., J. P. Molin, and J. Jasper. 2012. "Active Crop Sensor to Detect Variability of Nitrogen Supply and Biomass on Sugar cane Fields." *Precision Agriculture* 13(1): 33–44.

Raij, B. van., Heitor Cantarella, José Antonio Quaggio, and A. M. C. Furlani. 1997. *Recomendações de Adubação e Calagem para o Estado de São Paulo. Fertilizer Recommendation for São Paulo State*, Campinas. Instituto Agrônomo de Campinas; Fundação IAC. (In Portuguese).

Renouf, M.a., M.K. Wegener, and L.K. Nielsen. 2008. "An Environmental Life Cycle Assessment Comparing Australian Sugar cane with US Corn and UK Sugar Beet as Producers of Sugars for Fermentation." *Biomass and Bioenergy* 32(12): 1144–1155.

Smeets, Edward M. W., Lex F. Bouwman, Elke Stehfest, Detlef P. van VUUREN, and Adam Posthuma. 2009. "Contribution of N<sub>2</sub>O to the Greenhouse Gas Balance of First-generation Biofuels." *Global Change Biology* 15(1): 1–23.

Sripada, Ravi P., Ronnie W. Heiniger, Jeffrey G. White, and Alan D. Meijer. 2006. "Aerial Color Infrared Photography for Determining Early In-Season Nitrogen Requirements in Corn." *Agronomy Journal* 98(4): 968-977.

Waclawovsky, Alessandro J, Paloma M Sato, Carolina G Lembke, Paul H Moore, and Glaucia M Souza. 2010. "Sugar cane for Bioenergy Production: An Assessment of Yield and Regulation of Sucrose Content." *Plant Biotechnology Journal* 8(3): 263–76.

Zhang, Chunhua, and John M. Kovacs. 2012. "The Application of Small Unmanned Aerial Systems for Precision Agriculture: a Review." *Precision Agriculture* 13(6): 693–712.

---

**C0199**

Magalhães, P.S.G., Sanches, G.M., Molin, J.P., Portz, G., Amaral, L., Kolln, O.T., Duft, G.D. "Potential Solution to Contribute for Sugar Cane Spatial Variability Management". EFITA-WCCA-CIGR Conference "Sustainable Agriculture through ICT Innovation", Turin, Italy, 24-27 June 2013.